



GLOBAL  
FINISHING  
SOLUTIONS

# PAINT BOOTH LIGHT FIXTURES

Built and assembled at the Global Finishing Solutions® (GFS) headquarters in Osseo, Wisconsin, GFS light fixtures provide a cost-effective and energy-efficient solution for your paint booth lighting needs. All GFS paint booths come complete with four or six-tube light fixtures to create an exceptionally bright spraying environment with minimal shadows. GFS also offers a full line of bulbs for simplified replacement.

## T5 LIGHT FIXTURES

T5 fluorescent fixtures and lamps feature excellent performance and efficiency. GFS offers four or six-tube inside-access T5 fixtures, specifically designed to fit the smaller diameter of T5 lamps. T5 fixtures and lamps are recommended for enclosures with high ceilings and booths located in areas that reach high temperatures.

### FEATURES

GFS T5 fixtures feature:

- Environmental responsibility when used with low mercury lamps
- Class 1, Division 2, Groups A-D ratings
- Interlock safety switch
- Enclosed and gasketed construction
- Easy lamp replacement and retrofits
- 54 watt ballast

T5 Fixture Part No.	Description	Length
LABW-14T5-D12	4-Tube Fixture	4 ft.
LABW-16T5-D12	6-Tube Fixture	4 ft.

High-output T5 fluorescent lamps feature:

- Brightness of approximately 5000 lumens
- Color rendering index of 85
- Color-correct lighting

T5 Lamp Part No.	Description	Length
230-285	T5 fixtures, 54 W	4 ft.



## T8 LIGHT FIXTURES

GFS offers four or six-tube T8 fixtures that work interchangeably with high output fluorescent or LED lamps. For additional information about our LED lamps, please see the LED T8 Paint Booth Lighting flyer. GFS offers fluorescent and LED lamps for our T8 fixtures for exceptional brightness and flexibility in your paint booth.

### FEATURES

GFS T8 fixtures feature:

- Energy-efficient, 32 watt electronic ballasts
- ETL and ETL-C listing
- Class 1, Division 2, Groups A-D ratings
- Interlock safety switch
- Enclosed and gasketed construction
- Twist-in lamp holders
- Easy lamp replacement and retrofits
- Template for installation into existing panels
- Optional corner enclosures
- 32 watt ballast

T8 Fixture Part No.	Description	Length
LABW12-4	4-Tube Fixture	4 ft.
LABW12-6	6-Tube Fixture	4 ft.
LAR12-4	4-Tube Fixture (for dual-skin panels)	4 ft.
LAR12-6	6-Tube Fixture (for dual-skin panels)	4 ft.

T8 fluorescent lamps feature:

- Brightness of approximately 2850 lumens
- Color rendering index of 85
- Color-correct lighting

T8 Lamp Part No.	Description	Length
230-281	T8 fixtures, 32 W	4 ft.

Consult your Global Finishing Solutions sales representative for details of required installation, concrete pit, electrical wiring, conduit, air piping, roof penetrations and automatic fire suppression. The equipment installation location should be reviewed and approved by the local authorities having jurisdiction. All designs, specifications and components are subject to change at the manufacturer's sole discretion at any time without notice. Data published herein is informational in nature and shall not be construed to warrant suitability of the unit for any particular purpose as performance may vary with the conditions encountered.