

ProTect Spray Booth Liner

ProTect is a spray booth liner (SBL). It consists of a 23μ white polyester carrier that has a specially designed adhesive on the exposed (after removal of the protective release liner) side and a removable adhesive that adheres to spray booth wall panels on the other side. This self-wound product is protected with a white glassine paper with a differential release liner. This liner is removed after application to the wall panels. ProTect (SBL) is a cost effective, non-fibrous and easy to use protective coating for spray booths. The non-stretchable polyester aids in its removability.

Typical Applications

ProTect is specifically designed for lining spray booths to capture over-spray and dust particles. It reduces static electricity and increases the lux level in the spray booth. We recommend that ProTect (SBL) should be removed and replaced after every 1000 hours of baking depending upon the frequency of use.

Directions for Use:

- The surface must be clean and dust free
- The film can be applied from the box
- The material is applied vertically to the wall panel using a squeegee
- When it has been firmed down the white liner is removed and another strip applied, which can be slightly overlapped onto the existing strip. Refer to the product application sheet for detailed application instructions.

Product Properties

Film Thickness	23μ (.9 mil)
Adhesive heat resistance	Up to 80 °C (176 °F)
Roll Size	1040mm x 100m (41" x 328')

Disclaimer

Specifications subject to change without notice. Published information concerning Drytac products is based upon research which the company believes to be reliable and accurate. Such information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Drytac does not accept liability for risks associated with the performance of the materials in application. All Drytac products are subjected to carefully quality control throughout the manufacturing process and are sold subject to Drytac standard conditions of sale.

Product Structure

