

T8 LED Fixtures & Lamps for Paint Booths

SPECIFICATIONS



LED FIXTURE FEATURES

- ETL and ETL-C listed
- Enclosed and gasketed construction
- Twist-in lamp holders
- Inside access
- Interlock safety switch
- Easy lamp replacement and retrofits
- Template for installation into existing panels
- Corner enclosure (optional)

CLASS 1, DIVISION II - GROUPS A, B, C & D

These light fixtures were designed for locations in which volatile flammable liquids or gases are handled, processed or used. For an exceptional spraying environment, choose from six-tube, four-tube or corner fixture; tubes are included.

Fixture Models		Hertz	Voltage Range
Four-Tube	Six-Tube		
1025704	1025705 50/60		120 - 277

Fixture Dimensions		
Fixture*	Lens	Panel Opening
18.5 x 51.538	18.876 x 52.118	18 x 50.25

* Dimensions are approximate

T8 LED Lamps are an ideal energy saving choice for paint booths and finishing equipment.

LED LAMP FEATURES

- Glass-free and contains no mercury
- Significant energy savings — up to 40 percent* when compared to traditional fluorescent 32-watt T8 systems
- Virtually no ultraviolet or infrared light emitted
- Last longer than traditional fluorescent bulbs, providing up to a 50,000-hour life span
- Instant on, no flicker or buzz

*Actual savings depends on your system configuration.



GFS Part No.	Watt	Color Temperature	Brightness	CRI
1052766	17	5000 K	2100 Lumens	82